

BOSTIK SILMAX 2620 LIGHT GREY
Supersedes Date: 13-Nov-2019

Revision date 12-Mar-2021
Revision Number 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK SILMAX 2620 LIGHT GREY
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant.
Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik SA
420 rue d'Estienne d'Orves
92700 Colombes
FRANCE
Tel: +33 (0)1 49 00 90 00

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone No information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Signal word

None

Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH210 - Safety data sheet available on request

EUH208 - Contains Trimethoxyvinylsilane & N-(3-(trimethoxysilyl)propyl)ethylenediamine & 3-(Triethoxysilyl) propylamine & Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine. May produce an allergic reaction

2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing.

SAFETY DATA SHEET

BOSTIK SILMAX 2620 LIGHT GREY
Supersedes Date: 13-Nov-2019

Revision date 12-Mar-2021
Revision Number 2

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

| Chemical name | EC No | CAS No | Weight-% | Classification according to Regulation (EC) No. 1272/2008 [CLP] | Specific concentration limit (SCL) | REACH registration number |
|--|-----------|-------------|----------|--|---------------------------------------|---------------------------|
| Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine | 309-629-8 | 100545-48-0 | 1 - <2.5 | Skin Sens. 1 (H317) Aquatic Chronic 3 (H412) | Skin Sens. 1 :: C _≥ 25% | 01-2119979085-27-XXXX |
| Titanium dioxide | 236-675-5 | 13463-67-7 | 0.1- <1 | Carc. 2 (H351i) | | 01-2119489379-17-XXXX |
| Trimethoxyvinylsilane | 220-449-8 | 2768-02-7 | 0.1- <1 | Skin Sens. 1B (H317) Acute Tox. 4 (H332) Flam. Liq. 3 (H226) | | 01-2119513215-52-XXXX |
| 3-(Triethoxysilyl)propylamine | 213-048-4 | 919-30-2 | 0.1- <1 | Skin Corr. 1B (H314) Skin Sens. 1 (H317) Acute Tox. 4 (H302) | | 01-2119480479-24-XXXX |
| N-(3-(trimethoxysilyl)propyl)ethylenediamine | 217-164-6 | 1760-24-3 | 0.1- <1 | Eye Dam. 1 (H318) Skin Sens. 1B (H317) STOT SE 3 (H335) | | 01-2119970215-39-XXXX |

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice

Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.

SAFETY DATA SHEET

BOSTIK SILMAX 2620 LIGHT GREY
Supersedes Date: 13-Nov-2019

Revision date 12-Mar-2021
Revision Number 2

| | |
|------------------------------------|---|
| Inhalation | Remove to fresh air. If symptoms persist, call a doctor. |
| Eye contact | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| Skin contact | Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor. |
| Ingestion | Call a doctor immediately. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Small amounts of toxic methanol are released by hydrolysis. |
| Self-protection of the first aider | Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). |

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Thermal decomposition can lead to release of irritating gases and vapours.

Hazardous combustion products Carbon dioxide (CO₂).

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Wear self contained breathing apparatus for fire fighting if necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. Dyke

SAFETY DATA SHEET

BOSTIK SILMAX 2620 LIGHT GREY
Supersedes Date: 13-Nov-2019

Revision date 12-Mar-2021
Revision Number 2

far ahead of liquid spill for later disposal. Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep away from food, drink and animal feedingstuffs.

7.3. Specific end use(s)

Specific use(s)
Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

| Chemical name | European Union |
|---------------------------|---|
| Methyl alcohol 67-56-1 | TWA: 200 ppm TWA: 260 mg/m ³ * |

Derived No Effect Level (DNEL) No information available

| Derived No Effect Level (DNEL) | | | |
|--|----------------|--------------------------------|---------------|
| Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0) | | | |
| Type | Exposure route | Derived No Effect Level (DNEL) | Safety factor |
| worker Long term Local health effects | Inhalation | 3.35 mg/m ³ | |

| Titanium dioxide (13463-67-7) | | | |
|-------------------------------|----------------|-------------------------|---------------|
| Type | Exposure route | Derived No Effect Level | Safety factor |

SAFETY DATA SHEET

BOSTIK SILMAX 2620 LIGHT GREY
Supersedes Date: 13-Nov-2019

Revision date 12-Mar-2021
Revision Number 2

| | | | |
|---|------------|----------------------|--|
| | | (DNEL) | |
| worker Long term Local health effects | Inhalation | 10 mg/m ³ | |

| Trimethoxyvinylsilane (2768-02-7) | | | |
|--|----------------|--------------------------------|---------------|
| Type | Exposure route | Derived No Effect Level (DNEL) | Safety factor |
| worker Systemic health effects Long term | Inhalation | 27,6 mg/m ³ | |
| worker Systemic health effects Long term | Dermal | 3,9 mg/kg bw/d | |

| 3-(Triethoxysilyl) propylamine (919-30-2) | | | |
|--|----------------|--------------------------------|---------------|
| Type | Exposure route | Derived No Effect Level (DNEL) | Safety factor |
| worker Long term Systemic health effects | Inhalation | 59 mg/m ³ | |
| worker Short term Systemic health effects | Inhalation | 59 mg/m ³ | |
| worker Long term Systemic health effects | Dermal | 8.3 mg/kg bw/d | |
| worker Short term Systemic health effects | Dermal | 8.3 mg/kg bw/d | |

| N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3) | | | |
|---|----------------|--------------------------------|---------------|
| Type | Exposure route | Derived No Effect Level (DNEL) | Safety factor |
| Long term Systemic health effects worker | Inhalation | 35.5 mg/m ³ | |
| Long term Systemic health effects worker | Dermal | 5 mg/kg bw/d | |
| Short term Systemic health effects worker | Dermal | 5 mg/kg bw/d | |

| Derived No Effect Level (DNEL) | | | |
|---|----------------|--------------------------------|---------------|
| Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0) | | | |
| Type | Exposure route | Derived No Effect Level (DNEL) | Safety factor |
| Consumer Long term | Inhalation | 0.83 mg/m ³ | |

| Titanium dioxide (13463-67-7) | | | |
|--|----------------|--------------------------------|---------------|
| Type | Exposure route | Derived No Effect Level (DNEL) | Safety factor |
| Consumer Long term Systemic health effects | Oral | 700 mg/kg bw/d | |

| Trimethoxyvinylsilane (2768-02-7) | | | |
|--|----------------|-------------------------|---------------|
| Type | Exposure route | Derived No Effect Level | Safety factor |

SAFETY DATA SHEET

BOSTIK SILMAX 2620 LIGHT GREY
Supersedes Date: 13-Nov-2019

Revision date 12-Mar-2021
Revision Number 2

| | | | |
|--|------------|------------------------|--|
| | | (DNEL) | |
| Consumer Systemic health effects Long term | Inhalation | 18,9 mg/m ³ | |
| Consumer Systemic health effects Long term | Dermal | 7,8 mg/kg bw/d | |
| Consumer Systemic health effects Long term | Oral | 0,3 mg/kg bw/d | |

| 3-(Triethoxysilyl) propylamine (919-30-2) | | | |
|---|----------------|--------------------------------|---------------|
| Type | Exposure route | Derived No Effect Level (DNEL) | Safety factor |
| Consumer Long term Systemic health effects | Inhalation | 17 mg/m ³ | |
| Consumer Short term Systemic health effects | Inhalation | 17.4 mg/m ³ | |
| Consumer Long term Systemic health effects | Dermal | 5 mg/kg bw/d | |
| Consumer Short term Systemic health effects | Dermal | 5 mg/kg bw/d | |

| N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3) | | | |
|---|----------------|--------------------------------|---------------|
| Type | Exposure route | Derived No Effect Level (DNEL) | Safety factor |
| Long term Systemic health effects Consumer | Oral | 2.5 mg/kg bw/d | |
| Long term Systemic health effects Consumer | Inhalation | 8.7 mg/m ³ | |
| Long term Systemic health effects Consumer | Dermal | mg/kg bw/d | |

Predicted No Effect Concentration (PNEC) No information available.

| Predicted No Effect Concentration (PNEC) | |
|---|--|
| Titanium dioxide (13463-67-7) | |
| Environmental compartment | Predicted No Effect Concentration (PNEC) |
| Marine water | 0.0184 mg/l |
| Freshwater sediment | 1000 mg/kg |
| Freshwater | 0.184 mg/l |
| Marine sediment | 100 mg/kg |
| Soil | 100 mg/kg |
| Microorganisms in sewage treatment | 100 mg/l |
| Freshwater - intermittent | 0.193 mg/l |

| Trimethoxyvinylsilane (2768-02-7) | |
|--|--|
| Environmental compartment | Predicted No Effect Concentration (PNEC) |
| Freshwater | 0.34 mg/l |
| Marine water | 0.034 mg/l |
| Microorganisms in sewage treatment | 110 mg/l |

| 3-(Triethoxysilyl) propylamine (919-30-2) | | | |
|--|--|--|--|
|--|--|--|--|

SAFETY DATA SHEET

BOSTIK SILMAX 2620 LIGHT GREY
Supersedes Date: 13-Nov-2019

Revision date 12-Mar-2021
Revision Number 2

| | |
|---------------------------|--|
| Environmental compartment | Predicted No Effect Concentration (PNEC) |
| Freshwater | 0.33 mg/l |
| Marine water | 0.033 mg/l |

| N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3) | |
|---|--|
| Environmental compartment | Predicted No Effect Concentration (PNEC) |
| Freshwater | 0.062 mg/l |
| Marine water | 0.0062 mg/l |
| Freshwater - intermittent | 0.62 mg/l |
| Freshwater sediment | 0.05 mg/kg |
| Marine sediment | 0.005 mg/kg |
| Soil | 0.0075 mg/kg |
| Sewage treatment plant | 25 mg/l |

8.2. Exposure controls

| | |
|--|---|
| Engineering controls | Ensure adequate ventilation, especially in confined areas. |
| Personal protective equipment | |
| Eye/face protection | Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166. |
| Hand protection | Wear suitable gloves. Recommended Use: Neoprene™. Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374 |
| Skin and body protection | None under normal use conditions. |
| Respiratory protection | In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas. |
| Recommended filter type: | Organic gases and vapours filter conforming to EN 14387. White. Brown. |
| Environmental exposure controls | Do not allow uncontrolled discharge of product into the environment. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | | |
|--|------------------------------|-------------------------|
| Physical state | Liquid | |
| Appearance | Paste | |
| Colour | Grey | |
| Odour | Slight Characteristic | |
| Odour threshold | No information available | |
| Property | Values | Remarks • Method |
| pH | No data available | |
| pH (as aqueous solution) | No data available | |
| Melting point / freezing point | No data available | |
| Initial boiling point and boiling range | No data available | |
| Flash point | > 61 °C | CC (closed cup) |
| Evaporation rate | No data available | |
| Flammability | Not applicable for liquids . | |
| Flammability Limit in Air | | |
| Upper flammability or explosive limits | No data available | |
| Lower flammability or explosive limits | No data available | |
| Vapour pressure | 1100 | hPa @ 50 °C |
| Relative vapour density | No data available | |
| Relative density | No data available | |
| Water solubility | Reacts with water | |
| Solubility(ies) | No data available | |

SAFETY DATA SHEET

BOSTIK SILMAX 2620 LIGHT GREY
Supersedes Date: 13-Nov-2019

Revision date 12-Mar-2021
Revision Number 2

| | | |
|---------------------------|-------------------|-----------------------------|
| Partition coefficient | No data available | |
| Autoignition temperature | No data available | |
| Decomposition temperature | No data available | |
| Kinematic viscosity | No data available | |
| Dynamic viscosity | 7500 - 12500 Pa.s | Spindle ZU4 @ 1 rpm @ 23 °C |
| Explosive properties | No data available | |
| Oxidising properties | No data available | |

9.2. Other information

| | |
|-------------------|------------------------------|
| Solid content (%) | No information available |
| VOC Content (%) | |
| Density | 1.42 - 1.5 g/cm ³ |

SECTION 10: Stability and reactivity

10.1. Reactivity

| | |
|------------|------------------------------|
| Reactivity | Product cures with moisture. |
|------------|------------------------------|

10.2. Chemical stability

| | |
|-----------|---------------------------------|
| Stability | Stable under normal conditions. |
|-----------|---------------------------------|

Explosion data

| | |
|----------------------------------|-------|
| Sensitivity to mechanical impact | None. |
| Sensitivity to static discharge | None. |

10.3. Possibility of hazardous reactions

| | |
|------------------------------------|-------------------------------|
| Possibility of hazardous reactions | None under normal processing. |
|------------------------------------|-------------------------------|

10.4. Conditions to avoid

| | |
|---------------------|---|
| Conditions to avoid | Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition. |
|---------------------|---|

10.5. Incompatible materials

| | |
|------------------------|---|
| Incompatible materials | None known based on information supplied. |
|------------------------|---|

10.6. Hazardous decomposition products

| | |
|----------------------------------|--|
| Hazardous decomposition products | None under normal use conditions. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing. |
|----------------------------------|--|

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

| | |
|---------------------|---|
| Product Information | . |
| Inhalation | Based on available data, the classification criteria are not met. |
| Eye contact | Based on available data, the classification criteria are not met. |

SAFETY DATA SHEET

BOSTIK SILMAX 2620 LIGHT GREY
Supersedes Date: 13-Nov-2019

Revision date 12-Mar-2021
Revision Number 2

Skin contact May cause sensitisation in susceptible persons. Based on available data, the classification criteria are not met.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (inhalation-dust/mist) 278.848 mg/l

Component Information

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|--|--|--|---|
| Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine 100545-48-0 | LD50 >2000 mg/kg (Rattus) | | LC50 =5.05 mg/kg (Rattus) |
| Titanium dioxide 13463-67-7 | >10000 mg/kg (Rattus) | LD50 > 10000 mg/Kg | >5 mg/l |
| Trimethoxyvinylsilane 2768-02-7 | LD50 = 7120 -7236 mg/kg (Rattus) OECD 401 | = 3360 µL/kg (Oryctolagus cuniculus) | LC50 (4hr) 16.8 mg/l (Rattus) OECD TG 403 |
| 3-(Triethoxysilyl) propylamine 919-30-2 | LD50 = 1490 mg/kg (Rat, female) EPA OTS 798.1175 | LD50 = 4076 mg/kg (Oryctolagus cuniculus) EPA OTS 798.1100 | LC50 >144 mg/L (6h) Rat (Vapour) |
| N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3 | LD50 = 2295 mg/kg (Rattus) EPA OPPTS 870.1100 | LD50 > 2000 mg/kg (Oryctolagus cuniculus) EPA OPPTS 870.1200 | |

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. No classification is proposed, based on conclusive negative data. May cause sensitisation in susceptible persons.

| Product Information | | | |
|---------------------------------------|------------|----------------|--|
| Method | Species | Exposure route | Results |
| OECD Test No. 406: Skin Sensitisation | Guinea pig | Dermal | No sensitisation responses were observed |

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

| Chemical name | European Union |
|-----------------------------|----------------|
| Titanium dioxide 13463-67-7 | Carc. 2 |

SAFETY DATA SHEET

BOSTIK SILMAX 2620 LIGHT GREY
Supersedes Date: 13-Nov-2019

Revision date 12-Mar-2021
Revision Number 2

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

| Chemical name | Algae/aquatic plants | Fish | Toxicity to microorganisms | Crustacea | M-Factor | M-Factor (long-term) |
|--|---|--|----------------------------|--|----------|----------------------|
| Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine 100545-48-0 | EL50 (72h) >100 mg/L Algae (Pseudokirchneriella subcapitata) | LL50 (96h) >10mg/L (Onchorynchus mykiss) | - | EL50 (48h) >10mg/L Daphnia (Daphnia magna) | | |
| Titanium dioxide 13463-67-7 | LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203 | - | - | - | | |
| Trimethoxyvinylsilane 2768-02-7 | EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3 | LC50 (96h) = 191 mg/l (Oncorhynchus mykiss) | - | EC50(48hr) 168.7mg/l (Daphnia magna) | | |
| 3-(Triethoxysilyl) propylamine 919-30-2 | EC50 (72h) >1000 mg/L Green algae (desmodesmus subspicatus) (OECD TG 201) | LC50 (96h) >934 mg/L (Brachydanio rerio) (OECD TG 203) | - | EC50 (48h) =331 mg/L Daphnia magna (OECD TG 202) | | |
| N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3 | - | LC50 (96H) =597 mg/L (Danio rerio)Semi-static | - | EC50 (48h) =81mg/L Daphnia magna Static | | |

SAFETY DATA SHEET

BOSTIK SILMAX 2620 LIGHT GREY
Supersedes Date: 13-Nov-2019

Revision date 12-Mar-2021
Revision Number 2

12.2. Persistence and degradability

Persistence and degradability No information available.

| Component Information | | | |
|---|---------------|-------|--------------------------------|
| Trimethoxyvinylsilane (2768-02-7) | | | |
| Method | Exposure time | Value | Results |
| OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F) | 28 days | BOD | 51 % Not readily biodegradable |

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

| Chemical name | Partition coefficient | Bioconcentration factor (BCF) |
|---|-----------------------|-------------------------------|
| Trimethoxyvinylsilane 2768-02-7 | 1.1 | - |
| 3-(Triethoxysilyl) propylamine 919-30-2 | 1.7 | 3.4 |
| N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3 | -0.3 | - |

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment . The product does not contain any substance(s) classified as PBT or vPvB.

| Chemical name | PBT and vPvB assessment |
|---|--|
| Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine 100545-48-0 | The substance is not PBT / vPvB |
| Titanium dioxide 13463-67-7 | The substance is not PBT / vPvB PBT assessment does not apply |
| Trimethoxyvinylsilane 2768-02-7 | The substance is not PBT / vPvB |
| 3-(Triethoxysilyl) propylamine 919-30-2 | The substance is not PBT / vPvB |
| N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3 | The substance is not PBT / vPvB |

12.6. Other adverse effects

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Uncured product should be disposed of as hazardous waste. Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

SAFETY DATA SHEET

BOSTIK SILMAX 2620 LIGHT GREY
Supersedes Date: 13-Nov-2019

Revision date 12-Mar-2021
Revision Number 2

| | |
|--------------------------|---|
| Contaminated packaging | Handle contaminated packages in the same way as the product itself. |
| European Waste Catalogue | 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09 |
| Other information | Waste codes should be assigned by the user based on the application for which the product was used. |

SECTION 14: Transport information

Land transport (ADR/RID)

| | |
|---------------------------------|----------------|
| 14.1 UN number or ID number | Not regulated |
| 14.2 Proper Shipping Name | Not regulated |
| 14.3 Transport hazard class(es) | Not regulated |
| 14.4 Packing group | Not regulated |
| 14.5 Environmental hazards | Not applicable |
| 14.6 Special Provisions | None |

IMDG

| | |
|---|----------------|
| 14.1 UN number or ID number | Not regulated |
| 14.2 Proper Shipping Name | Not regulated |
| 14.3 Transport hazard class(es) | Not regulated |
| 14.4 Packing group | Not regulated |
| 14.5 Marine pollutant | NP |
| 14.6 Special Provisions | None |
| 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code | Not applicable |

Air transport (ICAO-TI / IATA-DGR)

| | |
|---------------------------------|----------------|
| 14.1 UN number or ID number | Not regulated |
| 14.2 Proper Shipping Name | Not regulated |
| 14.3 Transport hazard class(es) | Not regulated |
| 14.4 Packing group | Not regulated |
| 14.5 Environmental hazards | Not applicable |
| 14.6 Special Provisions | None |

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

| Chemical name | CAS No | Restricted substance per REACH Annex XVII |
|------------------|----------|---|
| Dioctyltin oxide | 870-08-6 | 20 |

SAFETY DATA SHEET

BOSTIK SILMAX 2620 LIGHT GREY
Supersedes Date: 13-Nov-2019

Revision date 12-Mar-2021
Revision Number 2

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

France

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) slightly hazardous to water (WGK 1)

TRGS - 510 Storage Class Storage Class 10 : Combustible liquids

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Not Listed

Denmark

Registration number(s) (P-no.) No information available

Norway

Registration number(s) (PRN-no.) No information available

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour

H302 - Harmful if swallowed

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H332 - Harmful if inhaled

H335 - May cause respiratory irritation

H412 - Harmful to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average)

SAFETY DATA SHEET

BOSTIK SILMAX 2620 LIGHT GREY
Supersedes Date: 13-Nov-2019

Revision date 12-Mar-2021
Revision Number 2

| | |
|---------|---|
| STEL | STEL (Short Term Exposure Limit) |
| Ceiling | Ceiling Limit Value |
| * | Skin designation |
| SVHC | Substance(s) of Very High Concern |
| PBT | Persistent, Bioaccumulative, and Toxic (PBT) Chemicals |
| vPvB | Very Persistent and very Bioaccumulative (vPvB) Chemicals |
| STOT RE | Specific target organ toxicity - Repeated exposure |
| STOT SE | Specific target organ toxicity - Single exposure |
| EWC | European Waste Catalogue |

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 12-Mar-2021

Indication of changes

Revision note SDS sections updated: 2, 3, 9, 11.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet